

Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

mollosil (Base + Catalyst)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Relining material for use in dentistry.

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH & Co. KG
Street: Carl-Zeiss-Strasse
Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

e-mail: post@detax.de
Internet: www.detax.de
Responsible Department: Emergency number: +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone +49 7243/510-0

number: This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

2.2. Label elements

Regulation (EC) No. 1272/2008

Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Containes polydimethylsiloxanes with functional groups. + fillers and pigment catalyst: additionally platinum complex compound.



according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 2 of 8

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to Regula	tion (EC) No. 1272/2008 [CLP]	•			
540-97-6	Dodecaemthylcyclohexasiloxane			< 0,5 %		
	208-762-8		01-2119517435-42			
541-02-6	Decamethylcyclopentasiloxane					
	208-764-9		01-2119511367-43			
556-67-2	octamethylcyclotetrasiloxane		< 0,5 %			
	209-136-7	014-018-00-1	01-2119529238-36			
	Flam. Liq. 3, Repr. 2, Aquatic Chronic 4; H226 H361f H413					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.


5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment.





according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 3 of 8

6.2. Environmental precautions

No special environmental measures are necessary. Clean contaminated objects and areas thoroughly observing environmental regulations.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Advice on storage compatibility

Do not store with acids, lyes, alcohols, metallic powders and metallic oxides (release of hydrogen is favoured).

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

7.3. Specific end use(s)

Silicone material for denture relinings.

For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 4 of 8

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Paste

Colour: base: gingiva coloured ,catalyst: white

Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range: not determined

Flash point: >100 °C DIN 51755

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Ignition temperature: >400 °C DIN 51794

Auto-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: >180 °C

Oxidizing properties

Not oxidizing.

Vapour pressure: <10 hPa

(at 20 °C)

Density (at 20 °C): 1,03 g/cm³ DIN 51757

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: 290000 mPa·s BROOKFIELD

(at 23 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: Acids, alkalis, alcohols, powdered metals or metal oxides with release of hydrogen.



according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 5 of 8

10.4. Conditions to avoid

Temperatures > 150°C/ 302 °F.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150°C/ 302 °F a small amount of formaldehyde can be released by oxidative degradation.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

For the product itself no toxicological data are available. In products with a comparable composition, a LD50 (orally, species rat) of > 5000 mg/kg has been found.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
540-97-6	Dodecaemthylcyclohexa	siloxane						
	oral	LD50 mg/kg	2000	Rat				
	dermal	LD50 mg/kg	2000	Rat				
541-02-6	Decamethylcyclopentasiloxane							
	oral	LD50 mg/kg	>24100	Rat	GESTIS			
	dermal	LD50 mg/kg	>2000	Rabbit		OECD 402		
	inhalation (4 h) vapour	LC50	8,67 mg/l	Rat		OECD 403		
556-67-2	octamethylcyclotetrasilox	kane						
	oral	LD50 mg/kg	4800	Rat		OECD 401		
	dermal	LD50 mg/kg	>2400	Rabbit		OECD 402		
	inhalation (4 h) vapour	LC50	36 mg/l	Rat	GESTIS	OECD 403		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].



Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 6 of 8

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation	-		-
556-67-2	octamethylcyclotetrasiloxane			
		3,7%	29	
	Not readily biodegradable (according to OECD criteria)			

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Dodecamethylcyclohexasiloxane (D6) fulfills the current criteria set forth under Annex XIII of the EU REACH Regulation for very persistent and very bioaccumulative substances (vPvB) and was included in the candidate list of substances of very high concern (SVHC). According to our knowledge of the state of the art, however, D6 cannot be compared with known persistent, bioaccumulative and toxic (PBT) and/or vPvB substances. The interpretation of the available data by the silicone industry reveals that scientific evidence obtained from field tests essentially points out that D6 does not lead to biomagnification in aquatic and terrestrial food chains. In air, D6 is decomposed by naturally occurring processes in the atmosphere. D-residues which do not decompose in this way in the air are not expected to accumulate from the air in water, the soil or living organisms.

Decamethylcyclopentasiloxane (D5) fulfills the current criteria set forth under Annex XIII of the EU REACH Regulation for vPvB substances and was included in the candidate list of SVHCs. According to our knowledge of the state of the art, however, D5 cannot be compared with known PBT and/or vPvB substances. The interpretation of the available data by the silicone industry reveals that scientific evidence obtained from field tests essentially points out that D5 does not lead to biomagnification in aquatic and terrestrial food chains. In air, D5 is decomposed by naturally occurring processes in the atmosphere. D-residues which do not decompose in this way in the air are not expected to accumulate from the air in water, the soil or living organisms.

Octamethylcyclotetrasiloxane (D4) fulfills the current criteria set forth under Annex XIII of the EU REACH Regulation for PBT and vPvB substances and was included in the candidate list of SVHCs. According to our knowledge of the state of the art, however, D4 cannot be compared with known PBT and/or vPvB substances. The interpretation of the available data by the silicone industry reveals that scientific evidence obtained from field tests essentially points out that D4 does not lead to biomagnification in aquatic and terrestrial food chains. In air, D4 is decomposed by naturally occurring processes in the atmosphere. D-residues which do not decompose in this way in the air are not expected to accumulate from the air in water, the soil or living organisms.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods



Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 7 of 8

Advice on disposal

Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

The mixture contains substances of very high concern (SVHC candidates):

Dodecamethylcyclohexasiloxane (D6), CAS no. 540-97-6 Decamethylcyclopentasiloxane (D5), CAS no. 541-02-6 Octamethylcyclotetrasiloxane (D4), CAS no. 556-67-2

National regulatory information

Water contaminating class (D): -- not water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.





according to Regulation (EC) No 1907/2006

mollosil (Base + Catalyst)

Revision date: 10.08.2018 Product code: 10488 Page 8 of 8

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour. H361f Suspected of damaging fertility.

H413 May cause long lasting harmful effects to aquatic life.

EUH210 Safety data sheet available on request.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

Identified uses

TF: Technical functions

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Gewerblich	-	-	-	-	-	-	-	2

 LCS: Life cycle stages
 SU: Sectors of use

 PC: Product categories
 PROC: Process categories

 ERC: Environmental release categories
 AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

mollosil Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesive for denture relinings for use in dentistry.

1.3. Details of the supplier of the safety data sheet

DETAX GmbH & Co. KG Company name: Street: Carl-Zeiss-Strasse Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

e-mail: post@detax.de Internet: www.detax.de Responsible Department: Emergency number: +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m. number:

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

ethyl acetate

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.



according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 2 of 9

P235 Keep cool.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use Carbon dioxide (CO2), Foam, Extinguishing powder to extinguish.

P501 Dispose of contents/ container in accordance with legal and national regulations.

Additional advice on labelling

According to Regulation (EC) 1272/2008, art.1 No. 5 (d) this product as a medical product must not be labelled!

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alkyl silicone resin in organic solvent.

Hazardous components

CAS No	Chemical name	Chemical name			
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
141-78-6	ethyl acetate	ethyl acetate			
	205-500-4	607-022-00-5	01-2119475103-46		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 3 of 9

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Adhesive for silicone based denture relinings.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters



according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 4 of 9

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: Ethyl acetate

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: 72 °C DIN 51356 Flash point: 3 °C DIN 51755

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 2,1 vol. %
Upper explosion limits: 11,5 vol. %

Ignition temperature: 460 °C DIN 51794

Auto-ignition temperature

Solid: not applicable



Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 5 of 9

Gas: not applicable

Decomposition temperature: >120 °C

Oxidizing properties

Not oxidizing.

Vapour pressure: 97 hPa

(at 20 °C)

Vapour pressure: 375 hPa

(at 50 °C)

Density (at 20 °C): 0,90 g/cm³ DIN 51757

Water solubility: partially miscible

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: 1 mPa·s BROOKFIELD

(at 23 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: combustible materials.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150°C/ 302 °F a small amount of formaldehyde can be released by oxidative degradation.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 6 of 9

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
141-78-6	ethyl acetate					
	oral	LD50	>2000 mg/kg	Rat		
	dermal	LD50	>2000 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50	>29,3 mg/l	Rat		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

	product to frot: Ecotoxic.					
CAS No	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	>100 mg/l		Salmo trutta fario (L) (Freshwater trout)	OECD 203
	Acute algae toxicity	ErC50	>100 mg/l		Desmodesmus subspicatus.	OECD 201
	Acute crustacea toxicity	EC50	>100 mg/l		Daphnia magna (Big water flea)	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation	•			
141-78-6	ethyl acetate				
	OECD 301D/ EEC 92/69/V, C.4-E	>70%	28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
141-78-6	ethyl acetate	0,68



according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 7 of 9

BCF

CAS No	Chemical name	BCF	Species	Source
141-78-6	ethyl acetate	30	Leuciscus idus (golden orfe)	

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identivied as PBT/ vPvB substances

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

UN 1866

D/E

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID) 14.1. UN number:

14.2. UN proper shipping name:	Resin solution
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Limited quantity:	5 L
Transport category:	2
Hazard No:	33

Other applicable information (land transport)

Flammable licquid

Tunnel restriction code:

Marine transport (IMDG)

14.1. UN number:	UN 1866
14.2. UN proper shipping name:	Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Marine pollutant:-Special Provisions:-

Limited quantity: 5 L/ 30 kg EmS: 5 L/ SE

Other applicable information (marine transport)

Flash point: 3°C c.c.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1866



Safety Data Sheet

according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 8 of 9

14.2. UN proper shipping name: Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3Limited quantity Passenger:1 L/ 30 kgPassenger LQ:Y341

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.





according to Regulation (EC) No 1907/2006

mollosil Adhesive

Revision date: 09.12.2016 Product code: 10528 Page 9 of 9

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lustrol gloss varnish (base)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lacquer for denture relinings for use in dentistry.

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH & Co. KG
Street: Carl-Zeiss-Strasse
Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

e-mail: post@detax.de
Internet: www.detax.de
Responsible Department: Emergency number:
+49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone +49 7243/510-0

number: This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Specific target organ toxicity - repeated exposure: STOT RE 2 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

xylene

Signal word: Danger

Pictograms:









according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 2 of 9

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P370+P378 In case of fire: Use Carbon dioxide (CO2), Foam, Extinguishing powder to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with local and national regulations.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Alkyl silicone resin in organic solvent.

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification according to Regulation (EC) No. 1272/2008 [CLP]					
1330-20-7	xylene					
	215-535-7 601-022-00-9 01-2119488216-32					
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H226 H332 H312 H315 H319 H335 H373 H304 H412					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).

4.2. Most important symptoms and effects, both acute and delayed

No information available.





according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent . Pyrophoric or self-heating substances.

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.



according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 4 of 9

7.3. Specific end use(s)

Component B of a silicone lacquer for use in dentistry. For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers		220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: FKM (fluoro rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing .

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid:
Colour: colourless
Odour: Benzene

Test method

pH-Value: not determined

Changes in the physical state



according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 5 of 9

Melting point: not determined

Initial boiling point and boiling range: 95 °C DIN 51356 Flash point: 10 °C DIN 51755

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 4 vol. %
Upper explosion limits: 32 vol. %

Ignition temperature: >450 °C DIN 51794

Auto-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: >150 °C

Oxidizing properties

Not oxidizing.

Vapour pressure: 29 hPa

(at 20 °C)

Vapour pressure: 1100 hPa

(at 50 °C)

Density (at 20 °C): 0,95 g/cm³ DIN 51757

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: 200 mPa·s BROOKFIELD

(at 23 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Reacts with: strong oxidising agents. The product may attack same plastic materials.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150°C/ 302 °F a small amount of formaldehyde can be released by oxidative degradation.



according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 6 of 9

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
1330-20-7	xylene						
	oral	LD50 mg/kg	3500	Rat	GESTIS		
	dermal LD50 >1700 Ra mg/kg		Rabbit	GESTIS			
			Rat	GESTIS			
	inhalation aerosol	ATE	1,5 mg/l				

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (xylene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name	nemical name							
	Aquatic toxicity	Dose	[h] [d] Species Source Method						
1330-20-7	xylene	rylene							
	Acute fish toxicity	LC50 2,661- 4,093 mg/l	96 h Oncorhynchus mykiss (Rainbow trout)						
	Acute crustacea toxicity EC50 3,82 mg/l		48 h						

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.



according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 7 of 9

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-20-7	xylene	3,15

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	0,6-15		

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identivied as PBT/ vPvB substances

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Limited quantity:5 L/ 30 kg

Transport category:

Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

Flammable licquid

Marine transport (IMDG)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Marine pollutant:-Special Provisions:-

Limited quantity: 5 L/ 30 kg



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Revision date: 23.07.2018 Product code: 10195 Page 8 of 9

EmS: F-E, S-E

Other applicable information (marine transport)

Flash point: 10°C c.c.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:UN 186614.2. UN proper shipping name:Resin solution

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 II

 Hazard label:
 3

Limited quantity Passenger: 1 L/ 30 kg Passenger LQ: Y341

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC).

Water contaminating class (D): 2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%



according to Regulation (EC) No 1907/2006

Lustrol gloss varnish (base)

Product code: 10195 Revision date: 23.07.2018 Page 9 of 9

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	

May cause damage to organs through prolonged or repeated exposure. H373

Harmful to aquatic life with long lasting effects. H412

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

Identified uses

	No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification	
ľ	1	Gewerblich	-	-	-	-	-	-	-	2	

LCS: Life cycle stages SU: Sectors of use PC: Product categories PROC: Process categories ERC: Environmental release categories AC: Article categories TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lustrol (Catalyst)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lacquer for denture relinings for use in dentistry.

1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH & Co. KG
Street: Carl-Zeiss-Strasse
Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

e-mail: post@detax.de
Internet: www.detax.de
Responsible Department: Emergency number: +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

1.4. Emergency telephone +49 7243/510-0

number: This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Acute toxicity: Acute Tox. 4
Acute toxicity: Acute Tox. 4

Serious eye damage/eye irritation: Eye Irrit. 2

Germ cell mutagenicity: Muta. 2 Reproductive toxicity: Repr. 1A

Specific target organ toxicity - repeated exposure: STOT RE 1 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements: Harmful if inhaled. Harmful if swallowed.

Causes serious eye irritation.

Suspected of causing genetic defects.

May damage fertility.

Causes damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

alkylstannonic siloxanes

Signal word: Danger

Pictograms:







according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 2 of 8

Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
 H319 Causes serious eye irritation.
 H341 Suspected of causing genetic defects.

H360F May damage fertility.

H372 Causes damage to organs (Thymus) through prolonged or repeated exposure if

swallowed.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Silicon-tin-compound with auxilliary matters.

Hazardous components

CAS No	Chemical name			Quantity		
	EC No	Index No	REACH No			
	Classification according to Regulation (EC) No. 1272/2008 [CLP]					
93925-42-9	alkylstannonic siloxanes					
	300-344-4	01-2119560586-30				
	Flam. Liq. 3, Muta. 2, Repr. 1, Acute Tox. 4, Acute Tox. 4, Eye Dam. 1, STOT RE 1, Aquatic Chronic 3; H226 H341 H360F H332 H302 H318 H372 H412					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. Immediately remove any contaminated clothing, shoes or stockings. Medical treatment necessary.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Let water be drunken in little sips (dilution effect). Seek immediately medical advice. Do not induce vomiting. In case of spontaneous vomiting take care of an unhindered flow out of the vomit (danger of suffocation).





according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 3 of 8

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations.

Advice on storage compatibility

Do not store with strong oxidising materials.

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

7.3. Specific end use(s)

Component A of a silicone lacquer for use in dentistry.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 4 of 8

For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber), FKM (fluoro rubber), CR (polychloroprene, chloroprene rubber)

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid:
Colour: colourless
Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: >200 °C DIN 51356 Flash point: >100 °C DIN 51755

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Ignition temperature: >300 °C DIN 51794

Auto-ignition temperature

Solid: not applicable
Gas: not applicable



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 5 of 8

Decomposition temperature: >250 °C

Oxidizing properties

Not oxidizing.

Vapour pressure: <1 hPa

(at 20 °C)

Density (at 20 °C): 0,97 g/cm³ DIN 51757

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: <80 mPa·s BROOKFIELD

(at 23 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with: strong oxidising agents.

10.4. Conditions to avoid

Higher temperatures advance the formation of flammable vapours, therefore don't expose the product to increased temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled.

For the product itself no toxicological data are available. In products with a comparable composition a LD50 (orally, species rat) of >2000 mg/kg has been found.

ATEmix calculated

ATE (oral) 1095,2 mg/kg; ATE (inhalative aerosol) 3,286 mg/l



according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 6 of 8

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
93925-42-9	alkylstannonic siloxanes									
		ATE mg/kg	500							
	inhalative vapour	ATE	11 mg/l							
	inhalative aerosol	ATE	1,5 mg/l							

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Based on a Bovine Corneal Permeability Study conducted in accordance with OECD Guideline No. 437 (July 2013), H318 is not shown.

EC regulation 1272/2008 annex 1, section 1.1.1.5: "For the purpose of classification of health hazards (part 3), the route of exposure, information on mechanisms and metabolism studies are useful for determining the relevance of effects in humans. If this information raises doubts as to their relevance in humans, in spite of the indisputable data legitimacy and quality, a lower classification may be justified. When there is scientific evidence that the mechanism or mode of action is not relevant to humans, the substance or mixture should not be classified."

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of causing genetic defects. (alkylstannonic siloxanes)

May damage fertility. (alkylstannonic siloxanes)

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs (Thymus) through prolonged or repeated exposure if swallowed. (alkylstannonic siloxanes)

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identivied as PBT/ vPvB substances

12.6. Other adverse effects

No information available.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 7 of 8

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 3 - highly water contaminating



according to Regulation (EC) No 1907/2006

Lustrol (Catalyst)

Revision date: 10.08.2017 Product code: 10534 Page 8 of 8

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure				
Acute Tox. 4; H332	Calculation method				
Acute Tox. 4; H302	Calculation method				
Eye Irrit. 2; H319					
Muta. 2; H341	Calculation method				
Repr. 1A; H360F	Calculation method				
STOT RE 1; H372	Calculation method				
Aquatic Chronic 3; H412	Calculation method				

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H302+H332 Harmful if swallowed or if inhaled.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H341 Suspected of causing genetic defects.

H360F May damage fertility.

H372 Causes damage to organs (Thymus) through prolonged or repeated exposure if

swallowed.

H412 Harmful to aquatic life with long lasting effects.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

Identified uses

No	Short title	SU main	SU	PC	PROC	ERC	AC	Specification
1	Gewerblich	-	-	-	-	-	-	2

SU main: Main user groups

PC: Product categories

ERC: Environmental release categories

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)