

according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

pattern eXpress®

Product group: UFI: Liquid component DJM1-MR3J-T60N-1NJQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resin (powder component) for embedding in material and material tests.

1.3. Details of the supplier of the safety data sheet

Company name:	AcrylX GmbH	
Street:	Industriestraße 7	
Place:	D-61191 Rosbach v.d.H.	
Telephone:	+49 (0) 6007 - 9382 300	Telefax:+49 (0) 6007 - 9382 390
e-mail:	info@acrylx.com	
Contact person:	Oliver Wesner	Telephone: 320
e-mail:	info@acrylx.com	
Internet:	www.acrylx.com	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

Danger

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Methyl methacrylate

1,4-Butandiol dimethacrylate

2,2'-[(4-methylphenyl)imino]bisethanol

Signal word:

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.



according to UK REACH Regulation

	pattern eXpress®	
Revision date: 29.03.2023	Product code: 1-842	Page 2 of 11
H412	Harmful to aquatic life with long lasting effects.	
Precautionary statemen	ts	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P302+P352	F ON SKIN: Wash with plenty of water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P370+P378	In case of fire: Use Foam, Extinguishing powder, Carbon dioxide (CO2) to extinguish.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container to as hazardous waste - in accordance with local and national legislation - suitable, approved incinerator for combustible organic waste.	

2.3. Other hazards

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture based on methyl methacrylate.

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
80-62-6	Methyl methacrylate			60 - < 65 %	
	201-297-1		01-2119452498-28		
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens	5. 1, STOT SE 3; H225 H315	H317 H335		
72869-86-4	7,7,9(or 7,9,9)-trimethyl-4,13-dioxo	-3,14-dioxa-5,12-diazahexa	decane-1,16-diyl bismethacrylate	10 - < 15 %	
	276-957-5		01-2120751202-68		
	Skin Sens. 1B, Aquatic Chronic 2;	H317 H411			
2082-81-7	1,4-Butandiol dimethacrylate	5 - < 10 %			
	218-218-1		01-2119967415-30		
	Skin Sens. 1; H317				
3077-12-1	2,2'-[(4-methylphenyl)imino]bisetha	nol		1 - < 5 %	
	221-359-1		01-2120791684-40		
	Acute Tox. 4, Eye Dam. 1; H302 H318				

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Cond	Specific Conc. Limits, M-factors and ATE				
80-62-6	201-297-1 Methyl methacrylate					
	inhalation: L0 mg/kg	inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg				
2082-81-7	218-218-1	1,4-Butandiol dimethacrylate	5 - < 10 %			
	dermal: LD50 = > 3000 mg/kg; oral: LD50 = > 10000 mg/kg					
3077-12-1	221-359-1	2,2'-[(4-methylphenyl)imino]bisethanol	1 - < 5 %			
	oral: LD50 =	> 300 mg/kg				

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Do NOT induce vomiting. Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Headache Dizziness Causes skin and eye irritation. Skin sensitisation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour. Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures



Revision date: 29.03.2023

pattern eXpress®

Product code: 1-842

Page 4 of 11

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

When using do not eat, drink, smoke, sniff. Use only in well-ventilated areas. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Caution! Transport usually takes place at temperatures above the flash point.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Protect from direct sunlight.

Hints on joint storage

Do not store together with: Material, oxygen-rich, Oxidising. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 5 of 11

DNEL/DMEL values

CAS No	Substance		-				
DNEL type		Exposure route	Effect	Value			
80-62-6	Methyl methacrylate						
Worker DNEL,	Worker DNEL, long-term inhalation 208 mg/m ³						
Worker DNEL,	long-term	dermal		17 mg/kg bw/day			

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

Wear suitable protective gloves. To protect against splashes: butyl; EN 374. To protect against immersion: butyl; 0.7 mm or thicker, EN 374. The suitability of gloves should be agreed with the manufacturer. Change gloves in the event of contamination or if the breakthrough time is exceeded. Resistance of the glove material: see information from the glove manufacturer.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

Wear suitable respiratory protection if technical measures are inadequate or not available and exposure is to be expected that exceeds the DNEL (derived exposure level below which the substance does not cause any harm to human health). A suitable breathing mask with filter type A (EN141 or EN405) is recommended. A self-contained breathing apparatus may be necessary if particularly high vapor concentrations are formed.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid		
Colour:	colourless		
Odour:	characteristic		
			Test method
Melting point/freezing point:		-48 °C	
Boiling point or initial boiling point and		100,3 °C	
boiling range:			
Flammability:		not applicable	
		not applicable	
Lower explosion limits:		2,1 vol. %	
Upper explosion limits:		12,5 vol. %	
Flash point:		10 °C	DIN 51755
Auto-ignition temperature:		435 °C	DIN 51794
Decomposition temperature:		not determined	
pH-Value:		not determined	
Water solubility: (at 20 °C)		15,3 g/L	
Solubility in other solvents			
not determined			
Partition coefficient n-octanol/water:		log Pow 1,38	
Vapour pressure:		37 hPa	



according to UK REACH Regulation

	pattern eXpress®	
Revision date: 29.03.2023	Product code: 1-842	Page 6 of 11
Density (at 20 °C): Relative vapour density:	0,94 g/cm³ not determined	
9.2. Other information		
Information with regard to physical hazard classes Self-ignition temperature Solid: Gas: Oxidizing properties Not oxidising.	s not applicable not applicable	
Other safety characteristics Evaporation rate: Solid content: Viscosity / dynamic: (at 20 °C) Further Information	not determined not determined 0,53 mPa⋅s	
none		

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable, Vapours can form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Can polymerise exothermically if heated, exposed to air, sunlight or by addition or free radical initiators. Protect from direct sunlight.

10.5. Incompatible materials

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Harmful if swallowed.

ATEmix tested

	Dose	Species	Source
LD50, oral	> 5000 mg/kg	Rat	
LD50, dermal	> 5000 mg/kg	Rabbit	
LC50, inhalation (vapour) (1 h)	29,8 mg/l	Rat	



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 7 of 11

CAS No	Chemical name									
	Exposure route	Dose		Species	Source	Method				
80-62-6	Methyl methacrylate	Methyl methacrylate								
	oral	LD50 mg/kg	>5000	Rat	OECD 401					
	dermal	LD50 mg/kg	>5000	Rabbit						
	inhalation vapour	LC50	29,8 mg/l	Rat						
2082-81-7	1,4-Butandiol dimethacry	late								
	oral	LD50 mg/kg	> 10000	Rat						
	dermal	LD50 mg/kg	> 3000	Rabbit						
3077-12-1	2,2'-[(4-methylphenyl)imir	no]bisethano	J							
	oral	LD50 mg/kg	> 300	Rat						

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Methyl methacrylate; 7,7,9(or 7,9,9)-trimethyl-4,13-dioxo-3,14-dioxa-5,12-diazahexadecane-1,16-diyl bismethacrylate; 1,4-Butandiol dimethacrylate)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation. (Methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Acute (short-term) fish toxicity



according to UK REACH Regulation

pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 8 of 11

CAS No	Chemical name	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
80-62-6	Methyl methacrylate	Methyl methacrylate							
	Acute fish toxicity	LC50 mg/l	> 79		Oncorhynchus mykiss (Rainbow trout)	OECD 203			
	Acute algae toxicity	ErC50 mg/l	> 110	72 h	Selenastrum capricornutum	OECD 201			
	Acute crustacea toxicity	EC50	69 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202			
	Crustacea toxicity	NOEC	37 mg/l		Daphnia magna (Big water flea)	OECD 202			
2082-81-7	1,4-Butandiol dimethacryl	ate		-					
	Acute fish toxicity	LC50 mg/l	32,5		Oncorhynchus mykiss (Rainbow trout)				
	Acute crustacea toxicity	EC50 mg/l	7,51	48 h	Daphnia magna (Big water flea)	OECD 211			
	Crustacea toxicity	NOEC mg/l	7,51		Selenastrum capricornutum				

12.2. Persistence and degradability

Biodegradable.

12.3. Bioaccumulative potential

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	Methyl methacrylate	1,38
2082-81-7	1,4-Butandiol dimethacrylate	3,1

12.4. Mobility in soil

Mobility in soil: No adsoption in soil or sediment.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste



pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 9 of 11

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID) 14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: Classification code: Limited quantity: Excepted quantity: Transport category: Hazard No: Tunnel restriction code:	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED 3 II 3 F1 1 L E2 2 339 D/E
Other applicable information (land trans SAPT: > 60 °C	port)
Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: Classification code: Limited quantity: Excepted quantity: Other applicable information (inland wate SAPT: > 60 °C	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED 3 II 3 F1 1 L E2 erways transport)
Marine transport (IMDG) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: Special Provisions: Limited quantity: Excepted quantity: EmS: Other applicable information (marine transformation (marine transformation))	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED 3 II 3 - 1 L E2 F-E, S-D INSPORT)
Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: Limited quantity Passenger: Passenger LQ: Excepted quantity: IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED 3 II 3 1 L Y341 E2 353 5 L



pattern eXpress®							
Revision date: 29.03.2023	Product code: 1-842	Page 10 of 11					
IATA-packing instructions - Cargo: 364 IATA-max. quantity - Cargo: 60 L Other applicable information (air transport) SAPT: > 60 °C							
 <u>14.6. Special precautions for user</u> Warning: Combustible liquid. <u>14.7. Maritime transport in bulk according to</u> not applicable 	Warning: Combustible liquid. 14.7. Maritime transport in bulk according to IMO instruments						
SECTION 15: Regulatory information							
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or m	<u>ixture</u>					
EU regulatory information Restrictions on use (REACH, annex XVII): Entry 3, Entry 40							
2010/75/EU (VOC):	64,5 % (606,3 g/l)						
2004/42/EC (VOC): Information according to 2012/18/EU (SEVESO III):	64,5 % (606,3 g/l) P5c FLAMMABLE LIQUIDS						
Additional information To follow: 850/2004/EC, 79/117/EEC, 6	89/2008/EC						
National regulatory information							
Employment restrictions:	Observe restrictions to employment for juveniles a work protection guideline' (94/33/EC). Observe er under the Maternity Protection Directive (92/85/Ef nursing mothers.	nployment restrictions					
Water hazard class (D):	3 - highly hazardous to water						
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.						
15.2. Chemical safety assessment							
Chemical safety assessments for subs	ances in this mixture were not carried out.						

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%



pattern eXpress®

Revision date: 29.03.2023

Product code: 1-842

Page 11 of 11

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 4; H302	
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to UK REACH Regulation

pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

pattern eXpress®

Product group: UFI:

Powder component W7X1-TR3E-E60K-S7E0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Resin (powder component) for embedding in material and material tests.

1.3. Details of the supplier of the safety data sheet

AcrylX GmbH	
Industriestraße 7	
D-61191 Rosbach v.d.H.	
+49 (0) 6007 - 9382 300	Telefax: +49 (0) 6007 - 9382 390
info@acrylx.com	
Oliver Wesner	Telephone: 320
info@acrylx.com	
www.acrylx.com	
	Industriestraße 7 D-61191 Rosbach v.d.H. +49 (0) 6007 - 9382 300 info@acrylx.com Oliver Wesner info@acrylx.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling dibenzoyl peroxide; benzoyl peroxide

Warning Signal word:

Pictograms:



Hazard statements	
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
Precautionary state	ments
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P501	Dispose of contents/container to as hazardous waste - in accordance with local and national legislation - suitable, approved incinerator for combustible organic waste.



pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 2 of 7

2.3. Other hazards

Contains methyl methacrylate, dibenzoyl peroxide. Can cause allergic reactions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture based on polymethyl methacrylates and catalyst.

Hazardous components

CAS No	Chemical name	Chemical name		Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regul	ation)		
9011-14-7	Acrylic polymer			95 - < 100 %
94-36-0	dibenzoyl peroxide; benzoyl p	peroxide		1 - < 5 %
	202-327-6		01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Sk H400 H410	in Sens. 1, Aquatic Acute 1, A	quatic Chronic 1; H241 H319 H317	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Get medical advice/attention if you feel unwell.

After inhalation

Provide fresh air.

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide, Carbon dioxide

5.3. Advice for firefighters



AcrylX GmbH

pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 3 of 7

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Avoid dust formation. Do not breathe dust. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information

Take up mechanically. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL

8.2. Exposure controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

Authorisation No.



pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 4 of 7

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. A suitable dust mask or respirator with filter type P1 or FFP1 (EN143 or EN149) may be suitable. In the unlikely event that particularly large amounts of dust are formed, a self-contained breathing apparatus may be appropriate.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Powder
Colour:	see packing
Odour:	characteristic
Melting point/freezing point:	ca. 110 °C
Boiling point or initial boiling point and	not determined
boiling range:	
Flammability:	not determined
	not applicable
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	> 250 °C
Auto-ignition temperature:	> 400 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	The study does not need to be conducted
	because the substance is known to be
	insoluble in water.
Solubility in other solvents	
Soluble in hydrocarbons.	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C): Bulk density (at 20 °C):	1,16 g/cm³ 700 - 750 kg/m³
Relative vapour density:	not determined
	not determined
9.2. Other information	
Information with regard to physical haz	ard classes
Self-ignition temperature	
Solid:	not determined
Gas: Oxidizing properties	not applicable
Not oxidising.	
5	
Other safety characteristics	
Evaporation rate: Solid content:	not determined 100 %
	100 %
SECTION 10: Stability and reactivity	

10.1. Reactivity

oxidising, Oxidising.

10.2. Chemical stability

May cause decomposition by long-term light influence. The product is stable under storage at normal ambient



pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 5 of 7

temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Combustible substance, Alkali metals, Alkaline earth metal, Heavy metals, Metal powder, Acid, Base.

10.4. Conditions to avoid

none

10.5. Incompatible materials

Keep away from combustible material.

10.6. Hazardous decomposition products

Formation of: Oxygen. Exothermal decomposition with formation of: Methyl methacrylate

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

Toxicological data are not available.

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (dibenzoyl peroxide; benzoyl peroxide)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.



pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 6 of 7

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Inland waterways transport (ADN)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Marine transport (IMDG)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No
14.6. Special precautions for user	
No information available.	
14.7. Maritime transport in bulk according	to IMO instruments
not applicable	
SECTION 15: Regulatory information	
15.1. Safety, health and environmental reg	ulations/legislation specific for the substance or mixture
EU regulatory information	
Information according to 2012/18/EU	Not subject to 2012/18/EU (SEVESO III)
(SEVESO III):	
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile
	work protection guideline' (94/33/EC).
Water hazard class (D):	2 - obviously hazardous to water
Skin resorption/Sensitization:	Causes allergic hypersensitivity reactions.

pattern eXpress®

Revision date: 21.11.2022

Product code: 1-841

Page 7 of 7

AcrylX GmbH

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)